

MATERIAL SAFETY DATA SHEET

PRODUCT NAME: PREMIXED STUCCO PATCH
 PRODUCT CODE: 2010

HMS CODES: H F R P
 0 2 0 C

SECTION I - MANUFACTURER IDENTIFICATION

MANUFACTURER'S NAME: Custom Building Products, Inc.
 ADDRESS: 6511 SALT LAKE AVE., BELL, CA. 90201
 EMERGENCY PHONE: (323) 582-0846 INFORMATION PHONE: (323) 582-0846
 DATE REVISED : 11-03-98 NAME OF PREPARER : STEVE TAYLOR

SECTION II - INGREDIENTS/SARA III INFORMATION

COMPONENTS	CAS NUMBER	OCCUPATIONAL EXPOSURE LIMITS		VAPOR PRESSURE mm Hg @	Wt. %
		OSHA PEL	ACGIH TLV		
CALCIUM CARBONATE/ LIMESTONE	1317-65-3		10 mg/M3	N/A	50
ALIPHATIC HYDROCARBON	8052-41-3	500	100PPM	2.0	68F <5.0%
SILICON DIOXIDE; AMORPHOUS, CRYSTALLINE	14808-60-7	10mg/M3	.3mg/M3	N/A	20

No toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372.

SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS

BOILING POINT: 212F SPECIFIC GRAVITY (H2O=1): 1.9
 VAPOR DENSITY: HEAVIER THAN AIR EVAPORATION RATE: SLOWER THAN ETHER
 SOLUBILITY IN WATER: MISCIBLE
 APPEARANCE AND ODOR: WHITE, SANDY PASTE; SLIGHT SOLVENT ODOR

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: NONE METHOD USED:
 FLAMMABLE LIMITS IN AIR BY VOLUME - LOWER: 1.0% UPPER: N/A

EXTINGUISHING MEDIA: FOAM, CO2, DRY CHEMICAL

SPECIAL FIREFIGHTING PROCEDURES
 NONE

UNUSUAL FIRE AND EXPLOSION HAZARDS
 MATERIAL CAN SPLATTER ABOVE 100C/212F. DRIED FILM CAN BURN.

===== SECTION V - REACTIVITY DATA =====

STABILITY: STABLE

CONDITIONS TO AVOID
NONE KNOWN

INCOMPATIBILITY (MATERIALS TO AVOID)
AVOID STRONG OXIDIZING AGENTS.

HAZARDOUS DECOMPOSITION OR BYPRODUCTS.

THERMAL DECOMPOSITION IN THE PRESENCE OF AIR MAY YIELD CARBON MONOXIDE AND/OR CARBON DIOXIDE.

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

===== SECTION VI - HEALTH HAZARD DATA =====

INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE
EXCESSIVE INHALATION OF VAPORS MAY CAUSE NASAL IRRITATION AND HEADACHE.

SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE
CONTACT WITH EYES CAN CAUSE IRRITATION, REDNESS, TEARING, AND BLURRED VISION.
PROLONGED SKIN CONTACT MAY CAUSE MODERATE IRRITATION.

SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE
WILL NOT BE ABSORBED THROUGH THE SKIN.

INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURES MAY CAUSE GASTROINTESTINAL IRRITATION

HEALTH HAZARDS (ACUTE AND CHRONIC)
THIS PRODUCT CONTAINS ONE OR MORE CHEMICALS KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER, BIRTH DEFECTS OR OTHER REPRODUCTIVE HARM. THE STATE OF CALIFORNIA (PROP. 65) REQUIRES THE ABOVE WARNING IN THE ABSENCE OF DEFINITIVE EVIDENCE TO PROVE THAT THE DEFINED RISKS DO NOT EXIST. WE BELIEVE THIS PRODUCT COMPLIES WITH ALL OTHER APPLICABLE STATE AND FEDERAL LAWS AND REGULATIONS GOVERNING MANUFACTURE, DISTRIBUTION AND INTENDED USE.

MUTAGENICITY: NTP? YES IARC MONOGRAPHS? YES OSHA REGULATED? YES
THERE IS SUFFICIENT EVIDENCE FOR THE CARCINOGENICITY OF CRYSTALLINE SILICA FROM EXPERIMENTAL ANIMALS, AND THAT THERE IS LIMITED EVIDENCE OF THE CARCINOGENICITY OF CRYSTALLINE SILICA TO HUMANS.

EDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE
PRE-EXISTING SKIN DISORDERS AND RESPIRATORY DISEASE.

EMERGENCY AND FIRST AID PROCEDURES

EYE CONTACT: IMMEDIATELY FLUSH EYES WITH WATER FOR 15 MINS. SEEK MEDICAL
ATTENTION IF IRRITATION PERSISTS.

SKIN CONTACT: WASH AREA WITH SOAP AND WATER. SEEK MEDICAL ATTENTION IF IRRITATION
RESULTS.

INHALED: IF AFFECTED, REMOVE PERSON TO FRESH AIR. SWALLOWED: IF INGESTED, INDUCE
VOMITTING. SEEK IMMEDIATE MEDICAL ADVICE AND/OR ATTENTION.

SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED
SPILLED MATERIAL MAY BE REMOVED WITH A SHOVEL AND INERT ABSORBANT.

WASTE DISPOSAL METHOD
DISPOSE OF PRODUCT IN ACCORDANCE WITH FEDERAL, STATE, AND LOCAL REGULATIONS.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING
STORE AWAY FROM ANY HEAT SOURCE.

OTHER PRECAUTIONS
NONE

SECTION VIII - CONTROL MEASURES

RESPIRATORY PROTECTION
IF EXPOSURE MAY EXCEED TLV RANGE, USE A NIOSH APPROVED RESPIRATOR TO PREVENT OVER-EXPOSURE.

VENTILATION
GENERAL MECHANICAL VENTILATION SHOULD BE SUFFICIENT.

PROTECTIVE GLOVES
THE USE OF CHEMICAL RESISTANT PLASTIC OR RUBBER GLOVES IS ADVISED TO PREVENT IRRITATION TO SENSITIVE INDIVIDUALS.

EYE PROTECTION
SAFETY GLASSES ARE RECOMMENDED.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT
ADEQUATE CLOTHING SHOULD BE WORN TO PREVENT FROM CONTACTING THE SKIN.

WORK/HYGIENIC PRACTICES
GOOD HOUSEKEEPING PROCEDURES SHOULD BE OBSERVED.

SECTION IX - DISCLAIMER

DISCLAIMER
THE INFORMATION PRESENTED HERE IS BELIEVED TO BE ACCURATE BUT IS NOT WARRANTED TO BE CORRECT, WHETHER ORIGINATING WITH THE COMPANY OR NOT. RECIPIENTS ARE ADVISED TO CONFIRM IN ADVANCE OF NEED, THAT THE INFORMATION IS CURRENT, APPLICABLE, AND RELEVANT TO THEIR CIRCUMSTANCES.