



# Material Safety Data Sheet

## Section 1. Chemical Product and Company Identification

**Product name** DYNA 143  
**Product use** Parts Cleaner  
**Product code** 0366  
**Date of issue** 10/25/13 **Supersedes** 11/08/10

### Emergency Telephone Numbers

**For MSDS Information:**

Technical Services Group  
Telephone (780) 453-8100  
(Business Hours 8:00am - 5:00pm)

**For Medical or Transportation Emergency**

CANUTEC (24 Hours)  
(613) 996-6666 - Call Collect

### Prepared By

Technical Services Group  
11627 178th Street  
Edmonton, Alberta T5S 1N6

## Section 2. Hazards Identification

### Emergency overview

CAUTION !

COMBUSTIBLE LIQUID AND VAPOR.

Combustible liquid. Keep away from heat, sparks and flame. Avoid breathing vapor or mist. Avoid contact with skin and clothing. Use only with adequate ventilation.

**NOTE: MSDS data pertains to the product as delivered in the original shipping container(s). Risk of adverse effects are lessened by following all prescribed safety precautions, including the use of proper personal protective equipment.**

### Acute Effects

### Routes of Entry

Eye contact, Skin, Inhalation.

#### Eyes

May cause eye irritation. Inflammation of the eye is characterized by redness, watering and itching.

#### Skin

May cause skin irritation. Skin inflammation is characterized by itching, scaling, or reddening.

#### Inhalation

Harmful by inhalation. Over-exposure by inhalation may cause respiratory irritation. Can cause central nervous system (CNS) depression. Pre-existing respiratory disorders may be aggravated by over-exposure to this product.

#### Ingestion

Aspiration hazard if swallowed. Can enter lungs and cause damage.

### Chronic effects

Prolonged skin contact may cause dermatitis with drying and cracking of skin. Skin which is repeatedly defatted by contact with this product may be more susceptible to irritation, infection or dermatitis.

**Additional Information: See Toxicological Information (Section 11)**

## Section 3. Composition/Information on Ingredients

### Name of Hazardous Ingredients

### CAS number

### % by Weight

LIGHT ALIPHATIC NAPHTHA; solvent naphtha (petroleum), medium aliphatics

64742-88-7

60 - 100

## Section 4. First Aid Measures

### Eye Contact

Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention if irritation occurs.

### Skin Contact

Flush affected skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur. Wash clothing before reuse. Clean shoes thoroughly before reuse.

### Inhalation

Move exposed person to fresh air. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. Get medical attention if adverse health effects persist or are severe.

**Ingestion** If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Never give anything by mouth to an unconscious person. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get immediate medical attention.

### Section 5. Fire Fighting Measures

**Flash Point** Closed cup: 62°C (143.6°F)  
[Pensky-Martens.]

**Flammable Limits** Lower: 1%  
Upper: 7%

**Flammability** Combustible liquid.

**Auto-ignition Temperature**

**Fire-Fighting Procedures** Use dry chemical, CO<sub>2</sub>, water spray (fog) or foam. Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

**Fire hazard** Combustible liquid. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. The vapor/gas is heavier than air and will spread along the ground. Vapors may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back.

**Products of Combustion** May emit toxic fumes under fire conditions. carbon oxides (CO, CO<sub>2</sub>)

**Explosion hazard** Not available.

### Section 6. Accidental Release Measures

**Spill Clean up** Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble or absorb with an inert dry material and place in an appropriate waste disposal container. Use spark-proof tools and explosion-proof equipment. Dispose of via a licensed waste disposal contractor.

### Section 7. Handling and Storage

**Handling** Put on appropriate personal protective equipment (see Section 8). Do not breathe vapor or mist. Do not ingest. Avoid contact with eyes, skin and clothing. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use non-sparking tools. Take precautionary measures against electrostatic discharges. Do not reuse container. Wash thoroughly after handling.

**Storage** Do not store above the following temperature: 49°C (120°F). Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Do not store in unlabeled containers. Keep out of the reach of children.

### Section 8. Exposure Controls/Personal Protection

#### Product name

#### Exposure limits

No exposure limit value known.

#### Personal Protective Equipment (PPE)

**Eyes** Recommended: Splash goggles.



**Hands and Body** Recommended: Neoprene gloves. Nitrile gloves. Rubber gloves.

**Respiratory** Use with adequate ventilation. Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective occupational exposure limits. Wear appropriate respirator when ventilation is inadequate. Approved/certified respirator with organic vapor cartridge.

### Section 9. Physical and Chemical Properties

**Physical State** Liquid.

**Color** Colorless.

**pH** Not available.

**Odor** Mild.

**Boiling Point** 187°C (368.6°F)

**Vapor Pressure** < 1.0 @ 20°C

**Specific Gravity** 0.79

**Vapor Density** 5.3 [Air = 1]

**Solubility** Insoluble in the following materials: cold water.

**Evaporation Rate** 0.14 (Butyl acetate. = 1)

**Freezing Point**

**VOC (Consumer)** 100% (789 g/L; 6.58 lbs/gal)

**Section 10. Stability and Reactivity**

<b>Stability and Reactivity</b>	The product is stable.
<b>Incompatibility</b>	Reactive or incompatible with the following materials: oxidizing materials. Keep away from heat, sparks and flame.
<b>Hazardous Polymerization</b>	Will not occur.
<b>Hazardous Decomposition Products</b>	Under normal conditions of storage and use, hazardous decomposition products should not be produced.

**Section 11. Toxicological Information**

**Carcinogenicity** No known significant effects or critical hazards. Ingredients: Not listed as carcinogen by OSHA, NTP or IARC.

**Acute Toxicity**

Not available.

**Section 12. Ecological Information**

**Environmental Effects** No known significant effects or critical hazards.

**Aquatic Ecotoxicity**

Not available.

**Section 13. Disposal Considerations****Waste Information**

Waste must be disposed of in accordance with applicable regulations. Consult your local or regional authorities for additional information.

**Waste Stream****Section 14. Transport Information**

Regulatory information	UN number	Proper shipping name	Classes	PG*	Label	Additional information
<b>TDG Classification</b>	Not regulated.	-	-	-		-
<b>IMDG Class</b>	Not available.	Not available.	Not available.	-		-

**NOTE: DOT classification applies to most package sizes. For specific container size classifications or for size exceptions, refer to the Bill of Lading with your shipment. Limited Quantity: Small quantities of controlled goods are not regulated as Dangerous Goods according to TDG regulations.**

PG\* : Packing group

**Section 15. Regulatory Information****Canada****WHMIS (Canada)**

Class B-3: Combustible liquid with a flash point between 37.8°C (100°F) and 93.3°C (200°F).

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

**Section 16. Other Information**

*To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.*